


## **CANAGES Alert II**

### **Gas Detection for Ventilation Control**

The GasAlert II control panel monitors up to 25 EC-Gold sensors for common alarms and relay interlocks for fans and other controls.

This gas monitoring system is designed for parking and service garages, warehouses, light industrial and municipal applications where it's unique wiring configuration offers an easy and economical installation.



Mix and match: carbon monoxide, nitrogen dioxide, oxygen, ammonia, propane, hydrogen and more

# GasAlert

#### **Features & Benefits**

- LED alarm status indication at main panel and at each sensor
- high, low, and high buzzer relay outputs for control interface
- adjustable time delay on AND off for all relays
- wall mount Type 1 metal or Type 4x polycarbonate enclosure
- buzzer with silence button
- electrochemical sensors minimize interference gases
- easy sensor mounting with external calibration and test features
- sensor push button to test interlocks

#### **Technical Specifications - Control Unit**

Operating Temperature -20°C to 40°C, indoor use

Power Input 24 vdc Standards UL, CSA

Enclosure Nema/Type 1 or Nema/Type 4x

#### **Technical Specifications - Sensor**


Operating Temperature -20°C to 40°C, indoor use
Power Input 24vdc, 0.1 amp each
Mounting surface mount

Standard Sensor gases available:

Carbon Monoxide, Hydrogen Sulfide, Chlorine, Ammonia, Nitrogen Dioxide, Broad Range Toxic, Combustibles and Refrigerants. Ask about our specialty gases.

#### WARRANTY

Standard 1 year warranty on electronics and sensor. Optional 2 and 3 year warranty on electronics and CO sensors when combined with Arjay calibration services.



Plug-in connectors and easy access sensors for fast maintenance.



Refer to EC-Gold brochure for sensor specifications

